



8x1 GigaBit LX to SX Regeneration Tap

Net Optics 8x1 GigaBit LX to SX Regeneration Taps solve the key physical layer challenges of multi-device monitoring for GigaBit LX networks. The built-in LX to SX media converter makes it easy to access LX links with SX devices. For a complete picture of network health, these Taps connect up to eight different GigaBit SX network management and security devices at any single GigaBit LX network location.

Keep your intrusion detection and prevention systems, protocol analyzers, RMON probes, and other security devices productive with a single Regeneration Tap. Maximize resources and save on access points when multiple devices can monitor link traffic simultaneously through a single Regeneration Tap.

Without an IP address, monitoring devices are isolated from the network, dramatically reducing their exposure to attacks. However, the monitoring device connected to the Tap still sees all full-duplex traffic as if it were in-line, including Layer 1 and Layer 2 errors.

For extra uptime protection, Net Optics Taps offer redundant power connections. Should the primary power source fail, the Tap automatically switches to the backup power source.

Passive, Secure Technology

- Enables real-time, simultaneous monitoring of a single GigaBit LX link with up to eight GigaBit SX monitoring devices
- Supports passive monitoring at 1000 Mbps
- Passes all traffic (including errors) from all layers for comprehensive troubleshooting
- No IP address is needed for the Tap or monitoring device, enhancing monitoring security
- Redundant power ensures monitoring uptime

Ease of Use

- LED indicators show redundant power, speed, link, and activity status
- Front-mounted connectors support easy installation and operation
- Connectors are perfectly angled to reduce cable strain
- Silk-screened application diagram illustrates all connections for easy deployment
- Optional custom monitoring cables support easy full-duplex monitoring by sending each side of the signal to a separate monitoring device NIC
- Tested and compatible with all major manufacturers' monitoring devices, including protocol analyzers, probes, and intrusion detection/prevention systems



Technical Specifications:

Operating:

Operating Temperature: 0°C to 40°C

Storage Temperature: -10°C to 70°C

Relative Humidity: 10% min, 95% max, non-condensing

Mechanical:

Redundant Power Supplies:

Input: 100-240VAC, 0.5A, 47-63Hz

Dimensions: 1.75" high x 10.5" deep x 17" wide

Splitter:

Split Ratio: 50/50

Fiber Type: Multimode Corning 62.5µm, wavelength 850nm

Insertion Loss: Monitoring Port: 4.5 dB

Fiber Type: Singlemode Corning 8.5µm, wavelength 1310nm

Insertion Loss: Network Port: 3.7 dB

Fiber Optic Interface:

Laser: Class I, eye-safe, laser emitter type. These Class I Lasers conform to the applicable requirements per US 21 CFR (J) and EN 60825-1, also UL 1950 applications.

Optical Transmitter Wave Length: 850nm nominal

Output Power: -9.5 dB min, -4 dB max

Optical Receiver Input Sensitivity: 0 dB min, -17 dB max

Optical Transmitter Wave Length: 1310nm nominal

Output Power: -10 dB min, -3 dB max

Optical Receiver Input Sensitivity: -3 dB min, -20 dB max

Connectors:

Monitoring Ports: (8) Multimode Duplex SC connectors

Network Ports: (2) Singlemode Duplex SC connectors

Certifications:

Fully RoHS compliant

Part Number	Description
RGN-LX/SX-IL8*	8x1 GigaBit LX to SX Regeneration Tap

*Also available in 4x1 and 8x1 models. All products include a 1 year manufacturer's warranty. An additional 1 or 2 year extended warranty may also be purchased.